



Maraton[®]

INDUSTRIAL PVC HOSES

sales@maraton.com.my



By MHM Consortium Sdn. Bhd.

TEL: +603 7734 4141 / 6012 320 6840

FAX: +603 7734 1945

Malaysia 

WWW.MARATON.COM.MY



PVC Steel Wire Reinforced Hose



- Light Duty Steel Wire Hose
- Heavy Duty Steel Wire Hose
- High-temperature Resistant Steel Wire Hose
- Low-temperature Resistant Steel Wire Hose
- Food Grade Steel Wire Hose
- Anti-static Steel Wire Hose
- Steel & Fiber Composite Steel Wire Hose

PVC Fiber Reinforced Hose



- Light Duty Fiber Hose
- Heavy Duty Fiber Hose
- Food Grade Fiber Hose
- Air Fiber Hose
- Special Air Fiber Hose
- High/low-temperature Resistant Fiber Hose
- Transparent Fiber Hose/Gas Fiber Hose

PVC Garden Reinforced Hose



- Garden Hose
- Special Garden Hose(4 Ply)
- Anti-torsion Hose
- Magic Hose

PVC Quality High Pressure LAYFLAT Hose



- Light Duty LAYFLAT Hose(4 Bar)
- Medium Duty LAYFLAT Hose(6 Bar)
- Heavy Duty LAYFLAT Hose(8/10 Bar)

PVC Other Hose



- PVC Helix Suction Hose
- TPU Steel Wire Reinforced Hose TPU
- PVC & Rubber Air Hose
- PVC Twin Welding Hose

PVC Steel Wire Reinforced Hose

Light Duty Steel Wire Hose



- Used for drawing and conveying water,oil and powder in factory,agriculture.
- Spiral steel wire reinforced incorporated within the wall of flexible pvc tubing.
- Suitable for usual pressure environment.
- High-quality low price,higher cost performance.
- Anti-uv.

Size I.D.	Size		Length	Max W.P.	Max B.P.	Weight
	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
3/8"	9	14	100	6	18	150
3/8"	10	15	100	6	18	160
1/2"	12	17	100	6	18	170
5/8"	15	21	100	6	18	250
3/4"	19	24	50	5	15	250
1"	25	29	50	4	12	220
1"	25	30	50	4	12	350
1-1/4"	32	36	50	3	9	400
1-1/4"	32	38	50	3	10	500
1-1/4"	32	39	50	3	10	600
1-1/2"	38	42	50	3	9	500
1-1/2"	38	44	50	3	9	600
1-1/2"	38	45	50	3	9	800
1-3/4"	45	50	50	3	9	600
1-3/4"	45	52	50	3	9	800
1-7/8"	48	54	50	3	9	800
1-7/8"	48	56	50	3	9	1000
2"	50	55.5	50	3	9	800
2"	50	57	50	3	9	1000
2"	50	60	50	3	9	1400
2-5/16"	58	65	30	2	6	1200
2-1/2"	64	72	30	2	6	1500
2-1/2"	64	75	30	2	6	2000
3"	76	84	30	2	6	1600
3"	76	87	30	2	6	2500
3-1/2"	90	102	20	2	6	3000
4"	102	112	20	2	6	2800
4"	102	113	20	2	6	3000

PVC Steel Wire Reinforced Hose

Heavy Duty Steel Wire Hose




- Used for drawing and conveying water, oil and powder in factory and agriculture.
- Suitable for high strength working environment like suction and discharge for sand.
- Good adaptability to hard weather condition and minus pressure, small bending radius, anti-abrasion.
- Passed the ROHS, PAHS test.
- Anti-uv.

Size I.D.	Size		Length m/roll	Max W.P. Bar	Max B.P. Bar	Weight g/m
	I.D. mm	O.D. mm				
1/4"	6	11	100	8	24	115
5/16"	8	14	100	8	24	150
3/8"	9	15	100	8	24	170
3/8"	10	16	100	8	24	200
1/2"	12	18	100	8	24	220
5/8"	15	22	50	6	18	300
3/4"	19	26	50	6	18	360
3/4"	20	26	50	6	18	320
7/8"	22	27	50	6	18	300
1"	25	33	50	5	16	540
1-1/4"	32	40	50	5	16	700
1-1/2"	38	48	50	5	15	1000
1-3/4"	45	56	50	5	15	1300
1-7/8"	48	59	50	5	15	1400
2"	50	62	50	5	15	1600
2-5/16"	58	69	40	4	12	1600
2-1/2"	64	78	30	4	12	2500
3"	76	90	30	4	12	3000
3-1/2"	90	108	20	4	12	4500
4"	102	116	20	4	12	4300
4-3/8"	110	123	20	3	9	4000
4-5/8"	117	133	10	3	9	5500
5"	127	143	10	3	9	6000
5-1/2"	140	156	10	3	9	6500
6"	152	170	10	2	6	8500
6-5/16"	160	176	10	2	6	8500
7"	180	196	10	2	6	8500
8"	200	224	10	2	6	12000
10"	254	286	10	2	6	20000

PVC Steel Wire Reinforced Hose

High-temperature Resistant Steel Wire Hose



- Hi-elasticity, Hi-strength zinc plated metal wire qualified special PVC synthesis materials.
- Used under 100°C condition, suitable for different high temperature environment.

Low-temperature Resistant Steel Wire Hose



- Hi-elasticity, hi-strength zinc plated metal wire, modified PVC and Silicon materials.
- Hose can maintain its good flexibility under the -40°C, suitable for different kinds of lower temperature environments.
- especially in north area.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
3/8"	10	16	100	8	24	200
1/2"	12	18	100	8	24	220
5/8"	15	22	50	6	18	300
3/4"	19	26	50	6	18	360
3/4"	20	26	50	6	18	320
7/8"	22	27	50	6	18	300
1"	25	33	50	5	16	540
1-1/4"	32	40	50	5	16	700
1-1/2"	38	48	50	5	15	1000
1-3/4"	45	56	50	5	15	1300
1-7/8"	48	59	50	5	15	1400
2"	50	62	50	5	15	1600
2-5/16"	58	69	40	4	12	1600
2-1/2"	64	78	30	4	12	2500
3"	76	90	30	4	12	3000
3-1/2"	90	108	20	4	12	4500
4"	102	116	20	4	12	4300

PVC Steel Wire Reinforced Hose

Food Grade Steel Wire Hose



- Food Grade hose can be used to convey foods like milk, beverage, jam and liquor which meets the FDA standard and pass REACH and EU Food Grade test.
- Used for food industry and health care industry.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/4"	6	11	100	8	24	115
5/16"	8	14	100	8	24	150
3/8"	9	15	100	8	24	170
3/8"	10	16	100	8	24	200
1/2"	12	18	100	8	24	220
5/8"	15	22	50	6	18	300
3/4"	19	26	50	6	18	360
3/4"	20	26	50	6	18	320
7/8"	22	27	50	6	18	300
1"	25	33	50	5	16	540
1-1/4"	32	40	50	5	16	700
1-1/2"	38	48	50	5	15	1000
1-3/4"	45	56	50	5	15	1300
1-7/8"	48	59	50	5	15	1400
2"	50	62	50	5	15	1600
2-5/16"	58	69	40	4	12	1600
2-1/2"	64	78	30	4	12	2500
3"	76	90	30	4	12	3000
3-1/2"	90	108	20	4	12	4500
4"	102	116	20	4	12	4300

PVC Steel Wire Reinforced Hose

Anti-static Steel Wire Hose



- Made of Hi-elasticity hi-strength zinc plated metal wire and high-quality PVC synthesis materials.
- The hose is clear and transparent with good flexibility and small bending radius.
- High-negative pressure resistant,high corrosion resistant,non-toxic and long life.
- Inserted the copper wire into the hose can avoid blockage of the internal flow because of the static electricity.
- Wildly used in mine,chemical plant and etc.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1"	25	33	50	5	16	540
1-1/4"	32	40	50	5	16	700
1-1/2"	38	48	50	5	15	1000
1-3/4"	45	56	50	5	15	1300
1-7/8"	48	59	50	5	15	1400
2"	50	62	50	5	15	1600
2-5/16"	58	69	40	4	12	1600
2-1/2"	64	78	30	4	12	2500
3"	76	90	30	4	12	3000
3-1/2"	90	108	20	4	12	4500
4"	102	116	20	4	12	4300

Steel & Fiber Composite Steel Wire Hose




- Use high-strength fibers and high-quality galvanized spring steel wire as reinforcement.
- The pressure resistance was enhanced 2-4 times than the single spiral wire reinforced hose.
- Inserted the copper wire into the hose can avoid blockage of the internal flow because of the static electricity.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1"	25	33	50	6	18	600
1-1/4"	32	41	50	5	15	800
1-1/2"	38	44	50	5	15	900
2"	50	60	50	5	15	1400
2-1/2"	64	75	40	4	12	1800
3"	75	88	40	4	12	2500
4"	102	116	30	4	12	4000

PVC Fiber Reinforced Hose

Light Duty Fiber Hose




- Supplying water & draining for equipment.
- High quality, low price, higher cost performance.
- Suitable for usual pressure environment.
- Passed the ROHS, PAHS test.
- Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
5/32"	4	8	100	10	50	49
13/64"	5	9	100	10	30	57
1/4"	6	10	100	10	40	65
5/16"	8	12	100	10	40	82
3/8"	10	14	100	9	35	98
1/2"	12	16	50	7	20	115
1/2"	12	17	50	8	24	150
1/2"	13	17	50	7	20	125
5/8"	15	19	50	6	20	140
5/8"	16	20	50	6	20	150
5/8"	16	21	50	7	21	190
3/4"	19	23	50	4	12	170
3/4"	19	24	50	4	12	220
3/4"	20	24	50	4	12	180
7/8"	22	27	50	4	12	250
1"	25	29	50	3	9	220
1"	25	30	50	4	12	281
1-1/4"	32	38	40	3	10	430
1-1/2"	38	45	40	3	10	590
1-3/4"	45	55	30	3	10	1020
2"	50	59	30	3	10	1010

PVC Fiber Reinforced Hose

Heavy Duty Fiber Hose




- Supplying water, gas, oil in agriculture and industry.
- Conveying solid particles, pulp in mines, engineering etc.
- Good adaptability to hard weather condition and minus pressure, small bending radius, anti-abrasion.
- Passed the ROHS, PAHS test.
- Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
13/64"	5	10	100	12	40	76
1/4"	6	11	100	12	36	87
5/16"	8	13	100	10	30	105
3/8"	10	15	100	10	30	130
1/2"	12	18	100	9	27	185
5/8"	16	22	50	8	24	230
3/4"	19	25	50	6	18	270
7/8"	22	28	50	5	15	305
1"	25	31	50	5	15	340
1-1/4"	32	40	40	4	12	590
1-1/2"	38	46	40	4	12	690
1-3/4"	45	56	30	4	12	1140
2"	50	62	30	4	12	1380
2-1/2"	64	78	20	4	12	2030
3"	76	92	20	4	12	2750

PVC Fiber Reinforced Hose

Food Grade Fiber Hose



- Food Grade hose can be used for conveying milk, beverage, distilled liquor, beer, jam and other food, which meets the FDA standard, and pass the REACH and Europe food grade test.
- Used for foodstuffs and sanitation industry.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/4"	6	10	100	10	40	65
5/16"	8	12	100	10	40	82
3/8"	10	14	100	9	35	98
1/2"	12	16	50	7	20	115
1/2"	12	17	50	8	24	150
1/2"	13	17	50	7	20	125
5/8"	15	19	50	6	20	140
5/8"	16	20	50	6	20	150
5/8"	16	21	50	7	21	190
3/4"	19	23	50	4	12	170
3/4"	19	24	50	4	12	220
3/4"	20	24	50	4	12	180
7/8"	22	27	50	4	12	250
1"	25	29	50	3	9	220
1"	25	30	50	4	12	281
1-1/4"	32	38	40	3	10	430
1-1/2"	38	45	40	3	10	590
1-3/4"	45	55	30	3	10	1020
2"	50	59	30	3	10	1010

PVC Fiber Reinforced Hose

Air Fiber Hose



- Generally used for air production equipment. ● Transfer compressed gas in garages and service stations.
- Used for automatic machines and gas station equipment. ● Used with pneumatic equipment and nail guns.
- Used for fire firefighting. ● Passed the ROHS, PAHS test. ● Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/4"	6.5	12	100	20	80	100
1/4"	6.5	12.5	100	30	95	115
5/16"	8.5	14	100	20	80	130
5/16"	8.5	14.5	100	30	90	140
3/8"	10	16	100	20	80	160
1/2"	13	20	50	20	75	240
5/8"	16	25	50	20	60	380
3/4"	19	28.5	50	20	50	460
1"	25	34.5	50	15	45	580
1-1/4"	32	44	40	15	45	940
1-1/2"	38	50	40	15	40	1085
2"	50	64	40	15	30	1640

Special Air Fiber Hose



- Adopt the advance new technology, made of the eco-friendly material and high density of polyester yarn.
- Good flexibility, durability against climate, high abrasion resistance and chemical resistance.
- Easy to handle, high pressure resistance. ● Passed the ROHS, PAHS test. ● Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/4"	6.5	13.5	100	40	160	142
5/16"	8.5	15.5	100	40	150	172
3/8"	9.5	16.5	100	40	120	185
3/8"	10	17	50	40	120	190
1/2"	12	20	50	30	100	260
5/8"	16	26	50	30	85	428
3/4"	19	29	50	25	75	490
1"	25	35	50	25	60	610

PVC Fiber Reinforced Hose



High-Temperature Resistant Fiber Hose

- Made of special PVC material and high strength fiber.
- High-temperature resistant fiber reinforced hose can be used in 100°C condition, suitable for different kinds of high temperature environments.

Low-Temperature Resistant Fiber Hose

- Made of special PVC material and high strength fiber.
- Low-temperature resistant fiber reinforced hose can be used in -40°C condition, suitable for different kinds of low temperature environments.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
13/64"	5	10	100	12	40	76
1/4"	6	11	100	12	36	87
5/16"	8	13	100	10	30	105
3/8"	10	15	100	10	30	130
1/2"	12	18	100	9	27	185
5/8"	16	22	50	8	24	230
3/4"	19	25	50	6	18	270
7/8"	22	28	50	5	15	305
1"	25	31	50	5	15	340
1-1/4"	32	40	40	4	12	590
1-1/2"	38	46	40	4	12	690
1-3/4"	45	56	30	4	12	1140
2"	50	62	30	4	12	1380
2-1/2"	64	78	20	4	12	2030
3"	76	92	20	4	12	2750

PVC Fiber Reinforced Hose


Gas Fiber Hose



- Supplying low pressure water,oil,gas in agriculture and industry.
- Especially for supplying LPG in household.
- High flexibility light weight and easy to handle.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
3/8"	9	15	100	2	6	147
1/2"	13	20	100	2	6	236

PVC Transparent Hose




- Made of non-toxic ingredients conforming to ROHS,REACH/FDA standards,passed the PAHS test.
- Flexible,Lightweight,anti-abrasion,heat resistant.
- Great Anti-UV ability.
- Can be restored to original shape even it squashed.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/8"	3	5	100	2	6	16
5/32"	4	6	100	2	6	20
3/16"	5	7	100	2	6	25
1/4"	6	8	100	1.5	5	28.5
5/16"	8	10	100	1.5	5	37
3/8"	10	12	100	1.5	4	45
1/2"	12	15	50	1.5	4	83
5/8"	15	18	50	1	3	101
3/4"	19	22	50	1	3	125
1"	25	29	50	1	3	220
1-1/4"	32	38	40	1	3	430
1-1/2"	38	44	40	1	3	500
2"	50	58	40	1	2.5	880

PVC Garden Reinforced Hose

Garden Hose



- Gardening, cleaning barns, parks, community.
- Irrigation flower garden and trees.
- Used for washing car.
- Passed the ROHS, PAHS test.
- Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/2"	12	15.4	30	5	15	90
1/2"	12	16	30	7	21	120
5/8"	15	19	30	5	15	145
5/8"	15	20	30	6	18	185
3/4"	19	23	30	4	12	178
3/4"	19	24	30	5	15	228
1"	25	29	30	3	9	229
1"	25	30	30	4	12	291

Special Garden Hose (4ply)




- Adopt the advance new technology, made of the eco-friendly material and high density of polyester yarn.
- Good flexibility, durability against climate, high abrasion resistance and chemical resistance.
- Easy handle, high pressure resistance.
- Passed the ROHS, PAHS test.
- Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/2"	12	16.4	30	7	21	130
1/2"	12	17	15	8	24	148
1/2"	12	17	30	8	24	148
5/8"	15	20	30	6	18	180
5/8"	15	21	30	7	21	220
3/4"	19	25	30	6	18	270
3/4"	19	26	30	6	20	320
1"	25	31	30	5	15	350

PVC Garden Reinforced Hose

Anti-torsion PVC Hose



- For garden irrigation, vehicle washing and daily washing.
- Three layers, made of top-quality material and polyester.
- Specialized design on reinforcement with knitted polyester, anti-torsion.
- Available in multiple colors.
- Flexible, Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/4"	6	10	100	10	40	66
5/16"	8	12	100	10	40	82
3/8"	10	14	100	9	35	100
1/2"	12	16	100	7	20	115
5/8"	15	19	100	6	20	140
3/4"	19	23	50	4	12	170
7/8"	22	27	50	4	12	250
1"	25	30	50	4	12	281
1-1/4"	32	38	50	4	12	430
1-1/2"	38	45	50	3	10	590
2"	50	59	50	3	10	1010

Magic Hose (Expandable Garden Hose)



- Light weight, good flexibility, bright color, smooth smearing layer, high pressure resistance, corrosion resistance and aging resistance.
- Hose can expand 3 times length with water and retract to its original length automatically.
- Made of high pressure-resistance durable latex inner tube and a folded durable super strong webbing outer covering.
- Equipped with 8-function spray gun, can spit out 8 different water shapes to meet kinds of using like watering flower and cleaning the cars.

Size	Size		Length	Max B.P.	Max W.P.
I.D.	I.D.	O.D.		AT 23°C	
Inch	mm	mm	m/roll	Bar	Bar
1/4"	6	9.5	25/7.5	6	12
1/4"	6	9.5	50/15	6	12
1/4"	6	9.5	75/22.5	6	12
1/4"	6	9.5	100/30	6	12

PVC High Pressure LAYFLAT Hose



- Irrigation in agriculture and transfer liquid in industry.
- Once-molded by extrude plastic. Small thickness, light weight, high resistance pressure.
- Anti-chemical, aging resistant.
- Environmental grade hose an meet REACH standard.
- Anti-uv.

Light Duty LAYFLAT Hose (4 Bar)

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	Wall Thickness		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
1"	25	1.3	100	4	15	150
1-1/4"	32	1.2	100	4	15	170
1-1/2"	38	1.2	100	4	15	190
2"	51	1	100	4	12	220
2-1/2"	64	1.1	100	4	12	300
3"	76	1.1	100	4	12	360
4"	103	1.25	100	4	12	550
5"	127	1.35	100	3.5	10	750
6"	153	1.35	100	3	9	900
8"	203	2	100	3	9	1600
10"	255	2.4	100	2.5	7	2600
12"	305	2.35	100	2	6	3000
14"	358	3	50	2	6	5000
16"	408	3	50	2	6	6000

Medium Duty LAYFLAT Hose (6 Bar)

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	Wall Thickness		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
3/4"	20	1.35	100	6	21	110
1"	25	1.3	100	6	21	160
1-1/4"	32	1.2	100	6	21	190
1-1/2"	38	1.2	100	6	21	220
1-1/2"	40	1.4	100	6	18	225
2"	51	1.35	100	6	18	300
2-1/2"	64	1.55	100	6	18	430
3"	76	1.5	100	6	18	500
4"	103	1.9	100	6	18	800
5"	127	2	100	6	18	1080
6"	153	2.4	100	6	18	1600
8"	203	2.6	100	5	15	2200

PVC High Pressure LAYFLAT Hose

Heavy Duty LAYFLAT Hose (8/10 Bar)



- Discharge sludge in agriculture, construction, industry, mining and marine service etc.
- Reinforced with specialized industrial polyester yarn, high pressure resistance.
- Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	Wall Thickness		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
3/4"	20	1.55	50	10	30	140
1"	25	1.8	50	10	30	200
1-1/4"	32	1.5	50	10	30	210
1-1/2"	38	1.7	50	10	30	290
1-1/2"	40	1.9	50	10	30	300
1-3/4"	45	2	50	10	30	350
2"	51	1.55	50	8	24	350
2"	51	1.8	50	10	30	420
2-1/2"	64	1.9	50	10	30	700
3"	76	2	50	8	24	660
3"	76	2.55	50	10	30	850
4"	103	2.25	50	8	24	1000
4"	103	2.7	50	10	30	1200
6"	153	3	50	8	24	2000
8"	203	3.2	50	6	18	2800

PVC Helix Suction Hose



Light Duty Suction Hose

- Suit low pressure watering in garden&household water supply.
- Colorful,light weight,flexible.
- Anti-UV.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
3/4"	19	23	30	6	18	230
1"	25	29	30	6	18	290
1-1/4"	32	36	30	6	18	350
1-1/2"	38	44	30	6	18	550
2"	50	54	30	5	15	550
2-1/2"	63	69	30	4	12	880
3"	75	81	30	3	9	1160
4"	100	108	30	3	9	1950
5"	125	135	10	3	9	3000

Heavy Duty Suction Hose

- Smooth inside and outside.
- High abrasion resistance and easy to transfer powder water and oil.
- Anti-UV.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.		AT 23°C		
Inch	mm	mm	m/roll	Bar	Bar	g/m
3/4"	19	25	30	8	24	280
1"	25	31	30	8	24	350
1-1/4"	32	40	30	8	24	500
1-1/2"	38	48	30	8	24	750
2"	50	58	30	7	21	920
2-1/2"	63	73	30	6	18	1300
3"	75	85	30	5	15	1650
4"	100	111	30	5	15	2550
5"	125	137	10	4	12	3300
6"	152	167	10	4	12	4200
8"	200	216	10	3	10	6400

PVC & Rubber Air Hose



- Made of quality synthesis material of PVC and rubber and polyester fiber.
- Various kinds of brilliant color.
- Light weight,more flexible,inner and outer,no twist under the low environment.
- Good durability,smooth inner and outer,no twist under the low environment.
- The ideal necessity for air pumps and air compressors.
- Anti-uv.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.				
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/4"	6.5	12	100	20	80	100
1/4"	6.5	12.5	100	30	95	115
5/16"	8.5	14	100	20	80	130
5/16"	8.5	14.5	100	30	90	140
3/8"	10	16	100	20	80	160
1/2"	13	20	50	20	75	240
5/8"	16	25	50	20	60	380
3/4"	19	28.5	50	20	50	460
1"	25	34.5	50	15	45	580
1-1/4"	32	44	40	15	45	940
1-1/2"	38	50	40	15	40	1085
2"	50	64	40	15	30	1640

PVC Twin Welding Hose



- Being widely used in welding machine, architecture and lacquer factory.
- Used for all kinds of metal-welding and cutting machines to transport Oxygen and Acetylene.
- Special formula compounding with good PVC resin and special materials.
- High pressure resistance, color resistance, good abrasion resistance and excellent resilience.
- Different color hose for easy using.

Size	Size		Length	Max W.P.	Max B.P.	Weight
I.D.	I.D.	O.D.				
Inch	mm	mm	m/roll	Bar	Bar	g/m
1/4"	6.5	12.5	28	20	60	120
5/16"	8	14	28	20	60	140
3/8"	10	16	28	20	60	165
1/2"	13	20	28	20	60	230

MHM Consortium Sdn.Bhd.

MHM Way

MHM is a professional hoses solution provider for global hydraulic and industrial fluid handling systems.

Utilizing its engineering resources, MHM develops different hoses categories for the worldwide market:

Hydraulic Hoses R1AT R2AT 1SN 2SN 1SC 2SC 1ST 2ST R3 R4 R5 R6 R7 R8 4SP 4SH R12 R13 R14 R15 R16 R17, Steam hose, Gasoline/Fuel hose, Pilot hose, Jetwasher hose.

Industrial Hoses Air/Water hose, Oil/Fuel hose, Water/Oil Suction & Discharge hose, Hot Water/Steam hose, Multipurpose hose, Tank Truck hose, Fuel/Diesel/Gasoline/Petroleum hose, Oxygen/Acetylene hose, Twin Welding hose, Propane/LPG hose, Sandblast hose, Cement hose, Plaster/Concrete hose, Slurry/Mud hose, Food hose, Chemical hose UHMWPE.

PTFE Hoses smooth and convoluted tube.

Hose Protector Spiral Hose Guard, Silicone Fiberglass Sleeve, Nylon Protective Sleeve.

Automotive Hoses Air Conditioning Hose SAE J2064, Power Steering Hose SAE J188, Air Brake hose SAE J1402, Hydraulic Brake hose SAE J1401, Fuel hose, Transmission Oil Cooler hose, Refrigerant Charging hose.

PVC Hoses Steel Wire Reinforced hose, Fiber Reinforced hose, Transparent hose, Food Grade hose, Garden hose, LAYFLAT hose, Helix Suction hose.

Hoses Accessories...

MHM also invests many resources on hoses management and services, aiming to provide long term and sustainable solutions for its customers.

MHM hoses have been serving more than 50 countries, with the best research team to explore the most optimized hose performance for different applications.

MHM brand is winning more and more recognition in many segments of the hoses solution industry.

MHM Mission & Vision

We are determined to make MHM a leading brand in the global hydraulic and industrial fluid handling systems.

To develop the MHM into an integrated hose solution supply and service platform offering comprehensive hose solutions to our customers.

MHM Value

•Quality - The key for our business sustainability •Integrity - The power of our business conduct •Commitment - The way to make our dream a reality •Togetherness - The spirit of growing together

MHM Strategy

•Market orientation •Brand image build up •Resources integration •IT reinforced operation

MHM R&D | Quality Assurance

Thanks to its strong engineering resources integration capacity, MHM provides customers most optimized hose solutions.

MHM attaches the greatest importance to the product quality.



The Global leader for Industrial PVC Hoses.

MHM Consortium Sdn. Bhd.

D-3A-12, Capital 4, Oasis Square, No. 2, Jalan PJU 1A / 7A,
47301 Petaling Jaya, Selangor. Malaysia.

Tel: +603 7734 4141, **Mobile:** +6012 320 6840

Fax: +603 7734 1945

Email : sales@maraton.com.my

Website: www.maraton.com.my