



Maraton[®]

RUBBER INDUSTRIAL HOSE

sales@maraton.com.my

The Global leader for Rubber Hoses.



By MHM Consortium Sdn. Bhd.

TEL: +603 7734 4141 / 6012 320 6840

FAX: +603 7734 1945

Made in Malaysia

WWW.MARATON.COM.MY

AIR HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4/8	12	20	300	60	900	120	400
1/4"	6.4	13	20	300	60	900	120	400
5/16"	7.9	15	20	300	60	900	100	330
3/8"	9.5	17	20	300	60	900	100	330
1/2"	12.7	21	20	300	60	900	100	330
5/8"	15.9	26	20	300	60	900	100	330
3/4"	19.1	29	20	300	60	900	100	330
7/8"	22.2	32	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330
1-1/4"	31.8	44	15	225	45	675	60	200
1-1/2"	38.1	54	15	225	45	675	60	200
2"	50.8	66	15	225	45	675	60	200



APPLICTION:

Oil mist resistant Air hose for versatile general industries and construction sites. NOT suitable for transfer of petroleum products.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, Synthetic Rubber, Oil mist resistant.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Yellow, Smooth, Synthetic Rubber, Weathering and Ozone Resistant

OPTIONAL REQUEST:

ISO 2398. Type 1.Class A

HOT AIR HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/4"	6.4	13	20	300	60	900	120	400
5/16"	7.9	15	20	300	60	900	120	400
3/8"	9.5	17	20	300	60	900	100	330
1/2"	12.7	21	20	300	60	900	100	330
5/8"	15.9	26	20	300	60	900	100	330
3/4"	19.1	29	20	300	60	900	100	330
3/4"	22.2	32	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330
1-1/4"	31.8	44	15	225	45	675	60	200
1-1/2"	38.1	54	15	225	45	675	60	200
2"	50.8	66	15	225	45	675	60	200



APPLICTION:

Heavy duty hot air hose is Specifically Designed to convey air for high temperature-applications.

TEMPERATURE:

-20 C(-4 F) to +100 C(+212 F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Black, Smooth, Synthetic Rubber, Weathering and Ozone Resistant

AIR BRAKE HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/4"	6.4	16	20	300	60	900	100	330
3/8"	9.5	19	20	300	60	900	100	330
1/2"	12.7	22	20	300	60	900	100	330


APPLICTION:

Designed for use in automotive air brake system.

TEMPERATURE:

-40°C(-40°F) to +93°C(+200°F)

TUBE:

Black, Smooth, EPDM rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Black, Smooth, EPDM rubber, heat and ozone resistant.

OPTIONAL REQUEST:

Standard SAE J1402 Type A

CAR HEATER HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/8"	9.5	17	10	150	30	450	100	330
1/2"	12.7	20	10	150	30	450	100	330
5/8"	15.9	24	10	150	30	450	100	330
3/4"	19.1	27	10	150	30	450	100	330
1"	25.1	35	10	150	30	450	100	330


APPLICTION:

Medium duty hose specially designed for the transfer of hot water in automobile's heating system.

TEMPERATURE:

-20°C(-4°F) to +100°C(+212°F)

TUBE:

Black, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Black, Smooth, Synthetic Rubber, Abrasion and Weather Resistant

MARINE FUEL HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/4"	6.4	15.8	3.5	50	14	200	100	330
5/16"	7.9	17.5	3.5	50	14	200	100	330
3/8"	9.5	20	3.5	50	14	200	100	330
1/2"	12.7	24	3.5	50	14	200	100	330



APPLICATION:

Designed with fire resistant property to convey fuel oil or diesel fuel aboard small craft including pleasure craft.

TEMPERATURE:

-25°C(-13°F) to +100°C(+212°F)

TUBE:

Black, Smooth, Synthetic rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Black, Smooth, Synthetic rubber, Weathering resistant and fire retardant.

OPTIONAL REQUEST:

Standard SAE J1527, Type A1 ISO 7840, A1 USCG

Standard SAE J1527, Type A1 ISO 7840, A1 USCG

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
5/8"	15.9	27	3.5	50	14	200	100	330
3/4"	19.1	30	3.5	50	14	200	100	330
1"	25.4	36	3.5	50	14	200	100	330

MARINE WET EXHAUST HOSE (Hardwall)								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	20	3	45	9	135	60	200
5/8"	15.9	23	3	45	9	135	60	200
3/4"	19.1	26	3	45	9	135	60	200
7/8"	22.2	30	3	45	9	135	60	200
1"	25.4	33.5	3	45	9	135	60	200
1-1/8"	28.6	38	3	45	9	135	60	200
1-3/16"	30.2	39	3	45	9	135	60	200
1-1/4"	31.8	40	3	45	9	135	60	200
1-5/16"	33.3	42	3	45	9	135	60	200



APPLICATION:

Light weight, flexible, hardwall hose for water cooled diesel engine exhaust gas System installed on a small craft less than 24m in length or pleasure yachts.

TEMPERATURE:

-30°C(-22°F) to +100°C(+212°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic cold, helix wire.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1-3/8"	34.9	43	3	45	9	135	60	200
1-1/2"	38.1	46	3	45	9	135	60	200
1-9/16"	39.7	48	3	45	9	135	60	200
1-5/8"	41.3	49	3	45	9	135	60	200
1-3/4"	44.5	53	3	45	9	135	60	200
1-7/8"	47.6	56	3	45	9	135	60	200
2"	50.8	59	3	45	9	135	60	200
2-1/8"	54	63	3	45	9	135	60	200
2-1/4"	57.2	67	3	45	9	135	60	200
2-3/8"	60.3	68	3	45	9	135	60	200
2-1/2"	63.5	72	3	45	9	135	60	200
2-5/8"	66.7	74	3	45	9	135	40	130
2-3/4"	69.9	78	3	45	9	135	40	130
2-7/8"	73	82	3	45	9	135	60	200
3"	76.2	85	3	45	9	135	60	200
3-1/8"	79.4	90	3	45	9	135	40	130
3-1/2"	88.9	99	3	45	9	135	60	200
4"	101.6	111	3	45	9	135	60	200
4-1/2"	114.3	126	3	45	9	135	30	100
5"	127	137	3	45	9	135	30	100
6"	152.4	163	3	45	9	135	30	100
8"	203.4	214	3	45	9	135	30	100
10"	254	264	3	45	9	135	12	40
12"	304.8	316	3	45	9	135	12	40

COVER:

Black, Corrugated (wrapped finish),
Systhetic Rubber, Weathering & Abra-
sion Resistant

OPTIONAL REQUEST:

Standard SAE J2006:03, Type R2:
Smooth (wrapped finish)

FREON GAS HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4.8	11	35	500	140	2000	100	330



APPLICTION:

Use in all air condition filling stations for automotive and other gas related industries.

TEMPERATURE:

-20°C(-4°F) to +65°C(+149°F)

TUBE:

Black, Smooth, Synthetic rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Red/Blue/Yellow, Smooth, Synthetic rubber, Weathering and resistant

MULTIPURPOSE HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4.8	12	20	300	60	900	120	400
1/4"	6.4	13	20	300	60	900	120	400
5/16"	7.9	15	20	300	60	900	100	330
3/8"	9.5	17	20	300	60	900	100	330
1/2"	12.7	21	20	300	60	900	100	330
5/8"	15.9	26	20	300	60	900	100	330
3/4"	19.1	29	20	300	60	900	100	330
7/8"	22.2	32	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330
1-1/4"	31.8	44	15	225	45	675	60	200
1-1/2"	38.1	54	15	225	45	675	60	200
2"	50.8	66	15	225	45	675	60	200



APPLICTION:

Light weight, flexible, hardwall hose for water cooled diesel engine exhaust gas System installed on a small craft less than 24m in length or pleasure yachts.

TEMPERATURE:

-30°C(-22°F) to +100°C(+212°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic cold, helix wire.

Low Pressure Textile Braided Hose								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4.8	10	20	300	60	900	100	330
1/4"	6.4	12.7	20	300	60	900	100	330
5/16"	7.9	14.2	20	300	60	900	100	330
3/8"	9.5	16	20	300	60	900	100	330
1/2"	12.7	19	20	300	60	900	100	330
5/8"	15.9	23	20	300	60	900	100	330
3/4"	19.1	26	20	300	60	900	100	330
1"	25.4	33.5	20	300	60	900	100	330



APPLICATION:

Designed for low pressure hydraulic oil lines and pneumatic lines. Meet Flame Resistant Certification.

TEMPERATURE:

-40°C(-40°F) to +100°C(+212°F)

TUBE:

Black, Smooth, Synthetic Rubber, Oil and Heat Resistant.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Black textile braided resistant weathering synthetic fibre.

FUEL / OIL HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4.8	12	20	300	60	900	120	400
1/4"	6.4	13	20	300	60	900	120	400
5/16"	7.9	15	20	300	60	900	100	330
3/8"	9.5	17	20	300	60	900	100	330
1/2"	12.7	21	20	300	60	900	100	330
5/8"	15.9	26	20	300	60	900	100	330
3/4"	19.1	29	20	300	60	900	100	330
7/8"	22.2	32	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330
1-1/4"	31.8	44	15	225	45	675	60	200
1-3/8"	34.9	47.8	15	225	45	675	60	200
1-1/2"	38.1	54	15	225	45	675	60	200
2"	50.8	66	15	225	45	675	60	200



APPLICATION:

Designed for the delivery of petroleum based products with aromatic content up to 50% for fuel connector service.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, NBR Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Black, smooth, synthetic rubber, weather and ozone resistant.

OPTIONAL REQUEST:

Anti-static wire / property.

FIRE FIGHTING HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	29	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330
1-1/4"	31.8	44	20	300	60	900	100	330


APPLICTION:

Designed with fire-fighting purposes for use with fixed systems.

TEMPERATURE:

-20°C(-4°F) to +60°C(+140°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Black, smooth, synthetic rubber, weathering and ozone resistant.

WASHDOWN HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	23	16	240	48	720	120	400
5/8"	15.9	27	16	240	48	720	100	330
3/4"	19.1	32	16	240	48	720	100	330
1"	25.4	39	16	240	48	720	100	330


APPLICTION:

Designed for hot water wash-down suitable for food processing industry, packing houses, bottling plants and breweries.

TEMPERATURE:

-20°C(-4°F) to +100°C(+212°F)

TUBE:

White, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

White, smooth, synthetic rubber, weathering and ozone resistant.

OPTIONAL REQUEST:

Standard F.D.A. Tile 21, 177.2600.

WATER HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4.8	12	10	150	30	450	120	400
1/4"	6.4	13	10	150	30	450	120	400
5/16"	7.9	15	10	150	30	450	100	330
3/8"	9.5	16	10	150	30	450	100	330
1/2"	12.7	20	10	150	30	450	100	330
5/8"	15.9	23.5	10	150	30	450	100	330
3/4"	19.1	27	10	150	30	450	100	330
7/8"	22.2	30	10	150	30	450	100	330
1"	25.4	34	10	150	30	450	100	330
1-1/4"	31.8	42	10	150	30	450	60	200
1-1/2"	38.1	50	10	150	30	450	60	200
2"	50.8	66	10	150	30	450	60	200



APPLICATION:

Designed for water and non-Corrosive fluids used in construction sites and light duty industrial applications.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Black smooth, synthetic rubber, weathering and ozone resistant.

LPG HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4.8	12	20	300	60	900	120	400
1/4"	6.4	14	20	300	60	900	120	400
5/16"	7.9	16	20	300	60	900	100	330
3/8"	9.5	17	20	300	60	900	100	330
1/2"	12.7	22	20	300	60	900	100	330



APPLICATION:

Designed for welding / cutting purpose in shipbuilding, civil works and other related industries.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Orange, smooth, synthetic rubber.

OPTIONAL REQUEST:

Standard ISO 3821 (formerly known as EN559); AS/NZS 1869:1996 Class C

SINGLE LINE WELDING HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4.8	12	20	300	60	900	120	400
1/4"	6.4	13	20	300	60	900	120	400
5/16"	7.9	15	20	300	60	900	100	330
3/8"	9.5	17	20	300	60	900	100	330
1/2"	12.7	21	20	300	60	900	100	330
5/8"	15.9	26	20	300	60	900	100	330
3/4"	19.1	29	20	300	60	900	100	330
7/8"	22.2	32	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330



APPLICTION:

Designed for welding, cutting and allied processes. Specific welding hose catering for oxygen, carbon dioxide, nitrogen, argon and fuel gases including acetylene, natural gas, methane and propane available on request.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Blue, Green, Red, Smooth, Synthetic Rubber.

OPTIONAL REQUEST:

Standard ISO 3821 (formerly known as EN559)

TWIN LINE WELDING HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/16"	4.8+4.8	12+12	20	300	60	900	120	400
1/4"	6.4+6.4	13+13	20	300	60	900	120	400
5/16"	7.9+7.9	15+15	20	300	60	900	100	330
5/16"+3/8"	7.9+9.5	16+16	20	300	60	900	100	330
3/8"	9.5+9.5	17+17	20	300	60	900	100	330



APPLICTION:

Extruded hose used for welding, cutting and allied processes.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic yarn.

COVER:

Red & Blue, smooth, synthetic rubber.

OPTIONAL REQUEST:

Standard ISO 3821 (formerly known as EN559)

AIR SEEDER HOSE (HARDWALL)

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	29	10	150	30	450	60	200
1"	25.4	35	10	150	30	450	60	200
1-1/4"	31.8	42	10	150	30	450	60	200
1-1/2"	38.1	48	10	150	30	450	60	200
2"	50.8	63	10	150	30	450	60	200
2-1/2"	63.5	76	10	150	30	450	60	200
3"	76.2	89	10	150	30	450	60	200
4"	101.6	118	10	150	30	450	60	200
6"	152.4	170	10	150	30	450	30	100


APPLICATION:

Hardwall hose designed for dry conveyance of seeds and other materials for medium duty abrasion and service.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, smooth, synthetic rubber, abrasion resistant.

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Black, smooth (wrapped finish). weathering and ozone resistant

BULK MATERIALS DISCHARGE HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
2"	50.8	68	10	150	30	450	60	200
2-1/8"	54	71	10	150	30	450	60	200
2-1/4"	57.2	74	10	150	30	450	60	200
2-3/8"	60.3	77	10	150	30	450	60	200
2-1/2"	63.5	81	10	150	30	450	60	200
2-5/8"	66.7	84	10	150	30	450	40	130
2-3/4"	69.9	88	10	150	30	450	40	130
2-7/8"	73	91	10	150	30	450	60	200
3"	76.2	94	10	150	30	450	40	200
3-1/8"	79.4	98	10	150	30	450	40	130
3-1/2"	88.9	107	10	150	30	450	60	200
4"	101.6	120	10	150	30	450	60	200
4-1/2"	114.3	134	10	150	30	450	30	100


APPLICATION:

Specially designed softwall hose for delivery of dry cement, sand, gravel and etc. Equipped with excellent rebound, durability and abrasion resistant properties.

TEMPERATURE:

-30°C(-22°F) to +70°C(+158°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic cold.

COVER:

Black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
5"	127	148	10	150	30	450	30	100
6"	152.4	175	10	150	30	450	30	100
8"	203.2	230	10	150	30	450	30	100
10"	254	281	10	150	30	450	12	40
12"	304.8	334	10	150	30	450	12	40

BULK MATERIALS SUCTION AND DISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
2"	50.8	68	10	150	30	450	60	200
2-1/8"	54	72	10	150	30	450	60	200
2-1/4"	57.2	75	10	150	30	450	60	200
2-3/8"	60.3	79	10	150	30	450	60	200
2-1/2"	63.5	82	10	150	30	450	60	200
2-5/8"	66.7	85	10	150	30	450	40	130
2-3/4"	69.9	89	10	150	30	450	40	130
2-7/8"	73	92	10	150	30	450	60	200
3"	76.2	95	10	150	30	450	60	200
3-1/8"	79.4	99	10	150	30	450	40	130
3-1/2"	88.9	108	10	150	30	450	60	200
4"	101.6	122	10	150	30	450	60	200
4-1/2"	114.3	136	10	150	30	450	30	100
5"	127	149	10	150	30	450	30	100
6"	152.4	176	10	150	30	450	30	100
8"	203.2	233	10	150	30	450	30	100
10"	254	284	10	150	30	450	12	40
12"	304.8	338	10	150	30	450	12	40



APPLICATION:

Specially designed hardwall hose for suction and delivery of dry cement, sand, gravel and etc. Equipped with excellent rebound, durability and abrasion resistant properties.

TEMPERATURE:

-30°C(-22°F) to +70°C(+158°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic cord and helix wire.

COVER:

Black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant.

OPTIONAL REQUEST:

Corrugated (wrapped finish).

SANDBLAST HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	28	10	150	30	450	60	200
1/2"	12.7	34	10	150	30	450	60	200
5/8"	15.9	26	10	150	30	450	60	200
5/8"	15.9	30	10	150	30	450	60	200
3/4"	19.1	34	10	150	30	450	60	200
3/4"	19.1	38	10	150	30	450	60	200
1"	25.4	38	10	150	30	450	60	200
1"	25.4	47	10	150	30	450	60	200
1-1/4"	31.8	42	10	150	30	450	60	200
1-1/4"	31.8	48	10	150	30	450	60	200
1-1/2"	38.1	58	10	150	30	450	60	200
2"	50.8	70	10	150	30	450	60	200
3"	76.2	96	10	150	30	450	60	200


APPLICATION:

Softwall abrasion resistant hose designed for the delivery of steel shots, sand and etc.

TEMPERATURE:

-40°C(-40°F) to +70°C(+158°F)

TUBE:

Black, smooth, high abrasion resistant, anti-staic.

REINFORCEMENT:

High strength synthetic cold.

COVER:

Black, smooth (wrapped finish), abrasion resistant

OPTIONAL REQUEST:

Standard ISO 3861.

BULK MATERIALS DISCHARGE HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	20	10	150	30	450	60	200
5/8"	15.9	23	10	150	30	450	60	200
3/4"	19.1	26	10	150	30	450	60	200
7/8"	22.2	30	10	150	30	450	60	200
1"	25.4	33.5	10	150	30	450	60	200
1-1/8"	28.6	38	10	150	30	450	40	130
1-3/16"	30.2	39	10	150	30	450	40	130
1-1/4"	31.8	40	10	150	30	450	60	200
1-5/16"	33.3	42	10	150	30	450	40	200


APPLICATION:

Light weight corrugated hardwall industrial hose designed for the extraction of waste dust. Fumes light particles and etc.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Tan, smooth, synthetic rubber.

REINFORCEMENT:

High strength synthetic cold and helix wire.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1-3/8"	34.9	43	10	150	30	450	60	200
1-1/2"	38.1	46	10	150	30	450	60	200
1-9/16"	39.7	48	10	150	30	450	60	200
1-5/8"	41.3	49	10	150	30	450	60	200
1-3/4"	44.5	53	10	150	30	450	60	200
1-7/8"	47.6	56	10	150	30	450	60	200
2"	50.8	59	10	150	30	450	60	200
2-1/8"	54	63	10	150	30	450	60	200
2-1/4"	57.2	67	10	150	30	450	60	200
2-3/8"	60.3	68	10	150	30	450	60	200
2-1/2"	63.5	72	10	150	30	450	60	200
2-5/8"	66.7	74	10	150	30	450	40	130
2-3/4"	69.9	78	10	150	30	450	40	130
2-7/8"	73	82	10	150	30	450	60	200
3"	76.2	85	10	150	30	450	60	200
3-1/8"	79.4	90	10	150	30	450	40	130
3-1/2"	88.9	99	10	150	30	450	60	200
4"	101.6	111	10	150	30	450	60	200
4-1/2"	114.3	126	10	150	30	450	30	100
5"	127	137	10	150	30	450	30	100
6"	152.4	163	10	150	30	450	30	100
8"	203.4	214	10	150	30	450	30	100
10"	254	264	10	150	30	450	12	40
12"	304.8	316	10	150	30	450	12	40

COVER:

 Tan, corrugated (wrapped finish)
 synthetic rubber.

COMPRESSED AIR HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	10	150	40	600	60	200
3/4"	19.1	28	10	150	40	600	60	200
1"	25.4	34	10	150	40	600	60	200
1-1/4"	31.8	42	10	150	40	600	60	200
1-1/2"	38.1	48	10	150	40	600	60	200
2"	50.8	62	10	150	40	600	60	200
2-1/2"	63.5	76	10	150	40	600	60	200
3"	76.2	89	10	150	40	600	60	200
4"	101.6	116	10	150	40	600	60	200



APPLICATION:

Softwall hose designed for general purpose compressed air applications with oil mist resistance.

TEMPERATURE:

-40°C(-40°F) to +70°C(+158°F)

TUBE:

Black, smooth, synthetic rubber, oil mist resistant.

REINFORCEMENT:

High strength synthetic cord

COVER:

Yellow, smooth (wrapped finish). weathering and ozone resistant.

OPTIONAL REQUEST:

Standard ISO 2398, Type 1, Class A.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	23	20	300	60	900	60	200
3/4"	19.1	30	20	300	60	900	60	200
1"	25.4	37	20	300	60	900	60	200
1-1/4"	31.8	46	20	300	60	900	60	200
1-1/2"	38.1	52	20	300	60	900	60	200
2"	50.8	68	20	300	60	900	60	200
2-1/2"	63.5	80	20	300	60	900	60	200
3"	76.2	92	20	300	60	900	60	200
4"	101.6	120	20	300	60	900	60	200

RADIATOR HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	3	45	9	135	60	200
5/8"	15.9	25	3	45	9	135	60	200
3/4"	19.1	28	3	45	9	135	60	200
7/8"	22.2	31	3	45	9	135	60	200
1"	25.4	34	3	45	9	135	60	200
1-1/8"	28.6	38	3	45	9	135	60	200
1-3/16"	30.2	40	3	45	9	135	60	200
1-1/4"	31.8	42	3	45	9	135	60	200
1-5/16"	33.3	43	3	45	9	135	60	200
1-3/8"	34.9	45	3	45	9	135	60	200
1-1/2"	38.1	48	3	45	9	135	60	200
1-9/16"	39.7	50	3	45	9	135	60	200
1-5/8"	41.3	52	3	45	9	135	60	200
1-3/4"	44.5	55	3	45	9	135	60	200
1-7/8"	47.6	59	3	45	9	135	60	200
2"	50.8	62	3	45	9	135	60	200
2-1/8"	54	66	3	45	9	135	60	200
2-1/4"	57.2	69	3	45	9	135	60	200
2-3/8"	60.3	72	3	45	9	135	60	200
2-1/2"	63.5	76	3	45	9	135	60	200
2-5/8"	66.7	78	3	45	9	135	40	130
2-3/4"	69.9	82	3	45	9	135	40	130
2-7/8"	73	86	3	45	9	135	60	40
3"	76.2	89	3	45	9	135	60	40
3-1/8"	79.4	94	3	45	9	135	40	130


APPLICATION:

Softwall hose for conveying hot water mixed with anti-freeze liquids in cooling systems.

TEMPERATURE:

-40°C(-40°F) to +100°C(+212°F)

TUBE:

Black, smooth, EPDM rubber.

REINFORCEMENT:

High strength synthetic cord.

COVER:

Black, smooth (wrapped finish). EPDM rubber.

OPTIONAL REQUEST:

Higher temperature up to 120°C (248°F)

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3-1/2"	88.9	103	3	45	9	135	60	200
4"	101.6	116	3	45	9	135	60	200
4-1/2"	114.3	129	3	45	9	135	30	100
5"	127	142	3	45	9	135	30	100
6"	152.4	167	3	45	9	135	30	100

CHEMICAL DISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	31	10	150	40	600	60	200
1"	25.4	37	10	150	40	600	60	200
1-1/4"	31.8	44	10	150	40	600	60	200
1-1/2"	38.1	51	10	150	40	600	60	200
2"	50.8	67	10	150	40	600	60	200
2-1/2"	63.5	79	10	150	40	600	60	200
3"	76.2	92	10	150	40	600	60	200
3-1/2"	88.9	105	10	150	40	600	60	200
4"	101.6	118	10	150	40	450	60	200



APPLICATION:

Softwall hose designed to handle a wide range of chemical products, sewage System and filtration plants.

TEMPERATURE:

-20°C(-4°F) to +65°C(+149°F)

TUBE:

White, Smooth, EPDM rubber.

REINFORCEMENT:

High strength synthetic cord.

COVER:

Blue, smooth (wrapped finish), EPDM rubber, resistant to chemical. weathering and ozone.

OPTIONAL REQUEST:

Anti-static wire.

CHEMICAL SUCTION AND DISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	31	10	150	40	600	60	200
1"	25.4	37	10	150	40	600	60	200
1-1/4"	31.8	44	10	150	40	600	60	200
1-1/2"	38.1	51	10	150	40	600	60	200
2"	50.8	67	10	150	40	600	60	200
2-1/2"	63.5	79	10	150	40	600	60	200
3"	76.2	92	10	150	40	600	60	200
3-1/2"	88.9	105	10	150	40	600	60	200
4"	101.6	118	10	150	40	600	60	200



APPLICTION:

Hardwall hose designed to handle a wide range of chemical products. sewage system and filtration plants.

TEMPERATURE:

-20°C(-4°F) to +65°C(+149°F)

TUBE:

White, smooth, EPDM rubber.

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Blue, smooth (wrapped finish), EPDM rubber, resistant to chemical. weath-ering and ozone.

OPTIONAL REQUEST:

Corrugated (wrapped finish); Anti-static wire.

UHMWPE CHEMICALDISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	31	10	150	40	600	60	200
1"	25.4	37	10	150	40	600	60	200
1-1/4"	31.8	44	10	150	40	600	60	200
1-1/2"	38.1	51	10	150	40	600	60	200
2"	50.8	67	10	150	40	600	60	200
2-1/2"	63.5	79	10	150	40	600	60	200
3"	76.2	92	10	150	40	600	60	200
3-1/2"	88.9	105	10	150	40	600	60	200
4"	101.6	118	10	150	40	600	60	200



APPLICTION:

Softwall hose designed with ultra-high molecular weight polyethylene tube. excellent in handling a wide range of chemicals, petroleum products and oils.

TEMPERATURE:

-30°C(-22°F) to +65°C(+149°F)

TUBE:

White, smooth, Ultra high molecular weight polyethylene (UHMWPE).

REINFORCEMENT:

High strength synthetic cold.

COVER:

Blue, smooth (wrapped finish), EPDM rubber, resistant to chemical. weath-ering and ozone.

OPTIONAL REQUEST:

Anti-static wire; Conductive UHMWPE film.

UHMWPE CHEMICAL SUCTION AND DISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	31	10	150	40	600	60	200
1"	25.4	37	10	150	40	600	60	200
1-1/4"	31.8	44	10	150	40	600	60	200
1-1/2"	38.1	51	10	150	40	600	60	200
2"	50.8	67	10	150	40	600	60	200
2-1/2"	63.5	79	10	150	40	600	60	200
3"	76.2	92	10	150	40	600	60	200
3-1/2"	88.9	105	10	150	40	600	60	200
4"	101.6	118	10	150	40	600	60	200



APPLICTION:

Hardwall hose designed with ultra-high molecular weight polyethylene tube. excellent in handling a wide range of chemicals, petroleum products and oils.

TEMPERATURE:

-30°C(-22°F) to +65°C(+149°F)

TUBE:

White, Smooth, Ultra high molecular weight polyethylene (UHMWPE)

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Blue, corrugated (wrapped finish), EPDM rubber, resistant to chemical, weathering and ozone.

OPTIONAL REQUEST:

Smooth (wrapped finish); Anti-static wire; Conductive UHMWPE film.

XLPE CHEMICAL DISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	31	10	150	40	600	60	200
1"	25.4	37	10	150	40	600	60	200
1-1/4"	31.8	44	10	150	40	600	60	200
1-1/2"	38.1	51	10	150	40	600	60	200
2"	50.8	67	10	150	40	600	60	200
2-1/2"	63.5	79	10	150	40	600	60	200
3"	76.2	92	10	150	40	600	60	200
3-1/2"	88.9	105	10	150	40	600	60	200
4"	101.6	118	10	150	40	600	60	200



APPLICTION:

Softwall hose designed with cross-linked polyethylene tube, excellent in handling a wide range of chemicals, petroleum products and oils.

TEMPERATURE:

-30°C(-22°F) to +65°C(+149°F)

TUBE:

White, smooth, Cross-linked polyethylene (XLPE).

REINFORCEMENT:

High strength synthetic cold.

COVER:

Green, smooth (wrapped finish), EPDM rubber, resistant to chemical, weathering and ozone.

OPTIONAL REQUEST:

Anti-static wire.

UHMWPE CHEMICAL SUCTION AND DISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	31	10	150	40	600	60	200
1"	25.4	37	10	150	40	600	60	200
1-1/4"	31.8	44	10	150	40	600	60	200
1-1/2"	38.1	51	10	150	40	600	60	200
2"	50.8	67	10	150	40	600	60	200
2-1/2"	63.5	79	10	150	40	600	60	200
3"	76.2	92	10	150	40	600	60	200
3-1/2"	88.9	105	10	150	40	600	60	200
4"	101.6	118	10	150	40	600	60	200



APPLICTION:

Hardwall hose designed with ultra-high molecular weight polyethylene tube. excellent in handling a wide range of chemicals, petroleum products and oils.

TEMPERATURE:

-30°C(-22°F) to +65°C(+149°F)

TUBE:

White, Smooth, Ultra high molecular weight polyethylene (UHMWPE)

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Blue, corrugated (wrapped finish), EPDM rubber, resistant to chemical, weathering and ozone.

OPTIONAL REQUEST:

Smooth (wrapped finish); Anti-static wire; Conductive UHMWPE film.

FOOD DISCHARGE HOSE (FOR FATTY FOODS)								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	24	10	150	30	450	60	200
3/4"	19.1	32	10	150	30	450	60	200
1"	25.4	38	10	150	30	450	60	200
1-1/4"	31.8	46	10	150	30	450	60	200
1-1/2"	38.1	52	10	150	30	450	60	200
2"	50.8	68	10	150	30	450	60	200
2-1/2"	63.5	80	10	150	30	450	60	200
3"	76.2	93	10	150	30	450	60	200
4"	101.6	120	10	150	30	450	60	200



APPLICTION:

FDA approved food hose designed for the delivery of fatty foods such as milk, edible oil, daily products & etc.

TEMPERATURE:

-20°C(-4°F) to +80°C(+176°F)

TUBE:

White, smooth, NBR food quality rubber.

REINFORCEMENT:

High strength synthetic cold.

COVER:

Red, smooth (wrapped finish), Synthetic rubber, oil and weathering resistant.

OPTIONAL REQUEST:

Standard F.D.A. Title 21, 177.2600.

FOOD SUCTION AND DISCHARGE HOSE (FOR FATTY FOODS)

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	24	10	150	30	450	60	200
3/4"	19.1	32	10	150	30	450	60	200
1"	25.4	38	10	150	30	450	60	200
1-1/4"	31.8	46	10	150	30	450	60	200
1-1/2"	38.1	52	10	150	30	450	60	200
2"	50.8	66	10	150	30	450	60	200
2-1/2"	63.5	80	10	150	30	450	60	200
3"	76.2	93	10	150	30	450	60	200
4"	101.6	120	10	150	30	450	60	200



APPLICTION:

FDA approved food hose designed for suction and delivery of fatty foods such as milk, edible oil, daily products etc.

TEMPERATURE:

-20°C(-4°F) to +80°C(+176°F)

TUBE:

White, Smooth, NBR food quality rubber.

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Red, smooth (wrapped finish),synthetic rubber, oil and weathering resistant.

OPTIONAL REQUEST:

Standard F.D.A. Title 21. 177.2600;
Corrugated (wrapped finish).

FOOD DISCHARGE HOSE (NON-FATTY FOODS)

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	24	10	150	30	450	60	200
3/4"	19.1	32	10	150	30	450	60	200
1"	25.4	38	10	150	30	450	60	200
1-1/4"	31.8	46	10	150	30	450	60	200
1-1/2"	38.1	52	10	150	30	450	60	200
2"	50.8	66	10	150	30	450	60	200
2-1/2"	63.5	80	10	150	30	450	60	200
3"	76.2	93	10	150	30	450	60	200
4"	101.6	120	10	150	30	450	60	200



APPLICTION:

FDA approved food hose designed for the delivery of aqueous foods such as wine, juice, soft drinks and other food-stuff.

NOT recommended for fatty foods.

TEMPERATURE:

-20°C(-4°F) to +80°C(+176°F)

TUBE:

White, smooth, EPDM food quality rubber.

REINFORCEMENT:

High strength synthetic cold.

COVER:

Blue, smooth (wrapped finish), Synthetic rubber, weathering resistant.

OPTIONAL REQUEST:

Standard F.D.A. Title 21, 177.2600.

FOOD SUCTION AND DISCHARGE HOSE (NON-FATTY FOODS)								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	24	10	150	30	450	60	200
3/4"	19.1	32	10	150	30	450	60	200
1"	25.4	38	10	150	30	450	60	200
1-1/4"	31.8	46	10	150	30	450	60	200
1-1/2"	38.1	52	10	150	30	450	60	200
2"	50.8	66	10	150	30	450	60	200
2-1/2"	63.5	80	10	150	30	450	60	200
3"	76.2	93	10	150	30	450	60	200
4"	101.6	120	10	150	30	450	60	200



APPLICATION:

FDA approved food hose designed for suction and delivery of aqueous foods such as wine, juice, soft drinks and other foodstuff.
NOT recommended for fatty foods.

TEMPERATURE:

-20°C(-4°F) to +80°C(+176°F)

TUBE:

White, smooth, EPDM food quality rubber.

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Blue, smooth (wrapped finish), Synthetic rubber, weathering resistant.

OPTIONAL REQUEST:

Standard F.D.A. Title 21, 177.2600;
Corrugated (wrapped finish).

MARINE FUEL HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1-1/2"	31.8	48	10	150	30	450	60	200
1-5/8"	41.3	51	10	150	30	450	60	200
1-7/8"	47.6	60	10	150	30	450	60	200
2"	50.8	63.5	10	150	30	450	60	200
2-3/8"	60.3	73	10	150	30	450	60	200



APPLICATION:

Hardwall hose designed for conveying gasoline and diesel fuel aboard small craft including pleasure craft.

TEMPERATURE:

-25°C(-13°F) to +100°C(+212°F)

TUBE:

Black, smooth, synthetic rubber.

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Black, smooth (wrapped finish), Synthetic rubber, weathering resistant.

OPTIONAL REQUEST:

Standard SAE J1527 Type A2 Style R2

MARINE WET EXHAUST HOSE (SOFTWALL)								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
7/8"	22.2	32	3	45	9	135	60	200
1"	25.4	35	3	45	9	135	60	200
1-1/8"	28.6	38	3	45	9	135	60	200
1-1/4"	31.8	43	3	45	9	135	60	200
1-5/16"	33.3	44	3	45	9	135	60	200
1-3/8"	34.9	46	3	45	9	135	60	200
1-1/2"	38.1	49	3	45	9	135	60	200
1-5/8"	41.3	54	3	45	9	135	60	200
1-3/4"	44.5	56	3	45	9	135	60	200
1-7/8"	47.6	59	3	45	9	135	60	200
2"	50.8	63.5	3	45	9	135	60	200
2-1/8"	54	66.5	3	45	9	135	60	200
2-1/4"	57.2	70	3	45	9	135	60	200
2-3/8"	60.3	74	3	45	9	135	60	200
2-1/2"	63.5	77.5	3	45	9	135	60	200
2-5/8"	66.7	82	3	45	9	135	40	130
2-7/8"	73	87	3	45	9	135	60	200
3"	76.2	90	3	45	9	135	60	200
3-1/8"	79.4	92	3	45	9	135	40	130
3-1/2"	88.9	104	3	45	9	135	60	200
4"	101.6	116	3	45	9	135	60	200
4-1/2"	114.3	130	3	45	9	135	30	100


APPLICATION:

Softwall hose designed for water cooled diesel engine exhaust gas systems installed on a small craft less than 24m in length or pleasure yachts.

TEMPERATURE:

-30°C(-22°F) to +100°C(+212°F)

TUBE:

Black, smooth, synthetic rubber.

REINFORCEMENT:

High strength synthetic cord.

COVER:

Black, smooth (wrapped finish). synthetic rubber, weathering & abrasion resistant.

OPTIONAL REQUEST:

130 Standard SAE J2006:03 Type R1.



APPLICATION:

Softwall hose specially designed with fire resistant and anti-static properties to convey air, stone dust and water in underground coal mines.

TEMPERATURE:

-15°C(-5°F) to +70°C(+158°F)

TUBE:

Pack, smooth, anti-static, synthetic rubber.

REINFORCEMENT:

High strength synthetic cord.

ELECTRICAL RESISTANCE:

Less than 1x10⁶f2/m.

COVER:

Black, smooth (wrapped finish). synthetic rubber, fire resistant and anti-static.

OPTIONAL REQUEST:

Standard AS 2660 Class A.



APPLICATION:

Designed ideally for protecting hose used in electronic, electrical and Sewage industries.

TEMPERATURE:

-25°C(-13°F) to +75°C(+167°F)

TUBE:

Black, smooth, abrasion resistant rubber blends.

COVER:

Black, smooth (wrapped finish), resistant rubber and weathering resistant.

FRAS AIR/WATER HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	17.5	260	70	1050	60	200
5/8"	15.9	25	17.5	260	70	1050	60	200
3/4"	19.1	28	17.5	260	70	1050	60	200
1"	25.4	34	17.5	260	70	1050	60	200
1-1/4"	31.8	42	17.5	260	70	1050	60	200
1-1/2"	38.1	48	17.5	260	70	1050	60	200
2"	50.8	62	17.5	260	70	1050	60	200
2-1/2"	63.5	76	17.5	260	70	1050	60	200
2-7/8"	73	86	17.5	260	70	1050	60	200
3"	76.2	89	17.5	260	70	1050	60	200
4"	101.6	116	17.5	260	70	1050	60	200

PROTECTIVE COVER HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
5/8"	15.9	19	-	-	-	-	40	130
3/4"	19.1	22	-	-	-	-	40	130
7/8"	22.2	25	-	-	-	-	40	130
1"	25.4	28	-	-	-	-	40	130
1-3/127"	26	28	-	-	-	-	40	130
1-1/8"	28.6	31	-	-	-	-	40	130
1-3/16"	30.2	33	-	-	-	-	40	130
1-1/4"	31.8	35	-	-	-	-	40	130
1-5/16"	33.3	36	-	-	-	-	40	130
1-3/8"	34.9	38	-	-	-	-	40	130
1-1/2"	38.1	41	-	-	-	-	40	130
1-9/16"	39.7	43	-	-	-	-	40	130
1-5/8"	41.3	45	-	-	-	-	40	130
1-3/4"	44.5	48	-	-	-	-	40	130
1-7/8"	47.6	51	-	-	-	-	40	130
2"	50.8	54	-	-	-	-	40	130

COMMONLY AVAILABLE UPON REQUEST

DIFFERENT DIAMETER DIFFERENT COLOR OF RUBBER DIFFERENT WORKING PRESSURE DIFFERENT LENGHT DIFFERENT TEMPERATURE

FUEL / OIL DISCHARGE HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	10	150	30	450	60	200
5/8"	15.9	25	10	150	30	450	60	200
3/4"	19.1	28	10	150	30	450	60	200
7/8"	22.2	31	10	150	30	450	60	200
1"	25.4	34	10	150	30	450	60	200
1-1/8"	28.6	38	10	150	30	450	60	200
1-3/16"	30.2	40	10	150	30	450	60	200
1-1/4"	31.8	42	10	150	30	450	60	200
1-5/16"	33.3	43	10	150	30	450	60	200
1-3/8"	34.9	45	10	150	30	450	60	200
1-1/2"	38.1	48	10	150	30	450	60	200
1-9/16"	39.7	50	10	150	30	450	60	200
1-5/8"	41.3	52	10	150	30	450	60	200
1-3/4"	44.5	55	10	150	30	450	60	200
1-7/8"	47.6	59	10	150	30	450	60	200
2"	50.8	62	10	150	30	450	60	200
2-1/8"	54	66	10	150	30	450	60	200
2-1/4"	57.2	69	10	150	30	450	60	200
2-5/16"	59	71.5	10	150	30	450	40	130
2-3/8"	60.3	72	10	150	30	450	60	200
2-1/2"	63.5	76	10	150	30	450	60	200
2-5/8"	66.7	78	10	150	30	450	40	130
2-3/4"	69.7	82	10	150	30	450	40	130
2-7/8"	73	86	10	150	30	450	60	200
3"	76.2	89	10	150	30	450	60	200
3-1/8"	79.4	94	10	150	30	450	40	130
3-1/2"	88.9	103	10	150	30	450	60	200
3-5/8"	92	106	10	150	30	450	40	130


APPLICATION:

Softwall hose designed for delivery of petroleum products with aromatic content up to 50% for fuel connector service.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, smooth, NBR rubber.

REINFORCEMENT:

High strength synthetic cord.

COVER:

Black, smooth (wrapped finish). synthetic rubber, weathering & oil resistant.

OPTIONAL REQUEST:

Anti-static wire.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3-3/4"	95	109	10	150	30	450	*	*
4"	101.6	116	10	150	30	450	60	200
4-3/8"	111	126	10	150	30	450	40	130
4-1/2"	114.3	129	10	150	30	450	30	100
5"	127	142	10	150	30	450	30	100
5-1/2"	140	154	10	150	30	450	30	100
6"	152.4	167	10	150	30	450	30	100
6-5/8"	168.3	184	10	150	30	450	30	100
7"	178	194	10	150	30	450	30	100
8"	203.2	219	10	150	30	450	30	100
8-5/8"	219.1	235	10	150	30	450	30	100
10"	254	272	5	75	15	225	12	40
12"	304.8	323	5	75	15	225	12	40

FUEL / OIL SUCTION AND DISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	10	150	30	450	60	200
5/8"	15.9	25	10	150	30	450	60	200
3/4"	19.1	29	10	150	30	450	60	200
7/8"	22.2	31	10	150	30	450	60	200
1"	25.4	35	10	150	30	450	60	200
1-1/8"	28.6	38	10	150	30	450	60	200
1-3/16"	30.2	40	10	150	30	450	60	200
1-1/4"	31.8	42	10	150	30	450	60	200
1-5/16"	33.3	43	10	150	30	450	60	200
1-3/8"	34.9	45	10	150	30	450	60	200
1-1/2"	38.1	48	10	150	30	450	60	200
1-9/16"	39.7	50	10	150	30	450	60	200



APPLICATION:

1-lardwall hose designed for suction and delivery of petroleum products with aromatic content up to 50% for fuel connector service.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, NBR Rubber.

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Black, smooth (wrapped finish), synthetic rubber, weathering and oil resistant.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1-5/8"	41.3	52	10	150	30	450	60	200
1-3/4"	44.5	56	10	150	30	450	60	200
1-7/8"	47.6	60	10	150	30	450	60	200
2"	50.8	63	10	150	30	450	60	200
2-1/8"	54	66	10	150	30	450	60	200
2-1/4"	57.2	69	10	150	30	450	60	200
2-5/16"	59	72.5	10	150	30	450	40	130
2-3/8"	60.3	74	10	150	30	450	60	200
2-1/2"	63.5	77	10	150	30	450	60	200
2-5/8"	66.7	80	10	150	30	450	40	130
2-3/4"	69.9	84	10	150	30	450	40	130
2-7/8"	73	88	10	150	30	450	60	200
3"	76.2	90	10	150	30	450	60	200
3-1/8"	79.4	95	10	150	30	450	40	130
3-1/2"	88.9	104	10	150	30	450	60	200
3-5/8"	92	107	10	150	30	450	40	130
3-3/4"	95	111	10	150	30	450	*	*
4"	101.6	118	10	150	30	450	60	200
4-3/8"	111	127	10	150	30	450	40	130
4-1/2"	114.3	130	10	150	30	450	30	100
5"	127	145	10	150	30	450	30	100
5-1/2"	140	158	10	150	30	450	30	100
6"	152.4	170	10	150	30	450	30	100
6-5/8"	168.3	186	10	150	30	450	30	100
7"	178	198	10	150	30	450	30	100
8"	203.2	224	10	150	30	450	30	100
8-5/8"	219.1	239	10	150	30	450	30	100
10"	254	278	10	150	30	450	12	40
12"	304.8	328	10	150	30	450	12	40

OPTIONAL REQUEST:

Corrugated (wrapped finish); Anti-static wire.

TANK TRUCK HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	10	150	30	450	60	200
5/8"	15.9	25	10	150	30	450	60	200
3/4"	19.1	29	10	150	30	450	60	200
7/8"	22.2	31	10	150	30	450	60	200
1"	25.4	35	10	150	30	450	60	200
1-1/8"	28.6	38	10	150	30	450	60	200
1-3/16"	30.2	40	10	150	30	450	60	200
1-1/4"	31.8	42	10	150	30	450	60	200
1-5/16"	33.3	43	10	150	30	450	60	200
1-3/8"	34.9	45	10	150	30	450	60	200
1-1/2"	38.1	48	10	150	30	450	60	200
1-9/16"	39.7	50	10	150	30	450	60	200
1-5/8"	41.3	52	10	150	30	450	60	200
1-3/4"	44.5	56	10	150	30	450	60	200
1-7/8"	47.6	60	10	150	30	450	60	200
2"	50.8	63	10	150	30	450	60	200
2-1/8"	54	66	10	150	30	450	60	200
2-1/4"	57.2	69	10	150	30	450	60	200
2-5/16"	59	72.5	10	150	30	450	40	130
2-3/8"	60.3	74	10	150	30	450	60	200
2-1/2"	63.5	77	10	150	30	450	60	200
2-5/8"	66.7	80	10	150	30	450	40	130
2-3/4"	69.7	84	10	150	30	450	40	130
2-7/8"	73	88	10	150	30	450	60	200
3"	76.2	90	10	150	30	450	60	200
3-1/8"	79.4	95	10	150	30	450	40	130
3-1/2"	88.9	104	10	150	30	450	60	200
3-5/8"	92	107	10	150	30	450	40	130


APPLICATION:

Hardwall hose designed for suction and delivery of a wide range of petroleum fuel with aromatic content up to 50% for tank trucks.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, smooth, synthetic rubber.

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Black, corrugated (wrapped finish). synthetic rubber, oil, fuel, weathering resistant.

OPTIONAL REQUEST:

Smooth (wrapped finish); wire.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3-3/4"	95	111	10	150	30	450	*	*
4"	101.6	118	10	150	30	450	60	200
4-3/8"	111	127	10	150	30	450	40	130
4-1/2"	114.3	130	10	150	30	450	30	100
5"	127	145	10	150	30	450	30	100
5-1/2"	140	158	10	150	30	450	30	100
6"	152.4	170	10	150	30	450	30	100

LOW TEMPERATURE TANK TRUCK HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	10	150	30	450	60	200
5/8"	15.9	25	10	150	30	450	60	200
3/4"	19.1	29	10	150	30	450	60	200
7/8"	22.2	31	10	150	30	450	60	200
1"	25.4	35	10	150	30	450	60	200
1-1/8"	28.6	38	10	150	30	450	60	200
1-3/16"	30.2	40	10	150	30	450	60	200
1-1/4"	31.8	42	10	150	30	450	60	200
1-5/16"	33.3	43	10	150	30	450	60	200
1-3/8"	34.9	45	10	150	30	450	60	200
1-1/2"	38.1	48	10	150	30	450	60	200
1-9/16"	39.7	50	10	150	30	450	60	200
1-5/8"	41.3	52	10	150	30	450	30	100
1-3/4"	44.5	56	10	150	30	450	30	100
1-7/8"	47.6	60	10	150	30	450	30	100
2"	50.8	63	10	150	30	450	30	100



APPLICATION:

Hardwall hose designed for suction and delivery of a wide range of petroleum fuel with aromatic content up to 50% for tank trucks. Suitable for low temperature.

TEMPERATURE:

-45 C(-49°F) to +70°C(+158°F)

TUBE:

Black, Smooth, synthetic Rubber.

REINFORCEMENT:

High strength synthetic cold and helix wire.

COVER:

Blue, corrugated (wrapped finish), synthetic rubber, oil, fuel, and weathering resistant.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
2-1/8"	54	66	10	150	30	450	60	200
2-1/4"	57.2	69	10	150	30	450	60	200
2-5/16"	59	72.5	10	150	30	450	40	130
2-3/8"	60.3	74	10	150	30	450	60	200
2-1/2"	63.5	77	10	150	30	450	60	200
2-5/8"	66.7	80	10	150	30	450	40	130
2-3/4"	69.9	84	10	150	30	450	40	130
2-7/8"	73	88	10	150	30	450	60	200
3"	76.2	90	10	150	30	450	60	200
3-1/8"	79.4	95	10	150	30	450	40	130
3-1/2"	88.9	104	10	150	30	450	60	200
3-5/8"	92	107	10	150	30	450	40	130
3-3/4"	95	111	10	150	30	450	*	*
4"	101.6	118	10	150	30	450	60	200
4-3/8"	111	127	10	150	30	450	40	130
4-1/2"	114.3	130	10	150	30	450	30	100
5"	127	145	10	150	30	450	30	100
5-1/2"	140	158	10	150	30	450	30	100
6"	152.4	170	10	150	30	450	30	100

OPTIONAL REQUEST:

Smooth (wrapped finish); Anti-static wire.



APPLICATION:

Heavy duty suction and discharge dock hose designed for transferring petroleum product from tankers and barges, bunkering service and industrial applications.

TEMPERATURE:

-20 C(-4 F) to +82°C(+180°F)

TUBE:

Black, smooth, synthetic rubber, suitable for aromatic content up to 50%.

REINFORCEMENT:

High Strength synthetic cold, helix wire and anti-static wires.

COVER:

Black, smooth (wrapped finish), synthetic rubber resistant to weathering, oil and sea water.

DOCK HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3"	76.2	96	17	225	68	1020	60	200
4"	101.6	126	17	225	68	1020	60	200
5"	127	155	17	225	68	1020	30	100
6"	152.4	185	17	225	68	1020	30	100
8"	203.2	242	17	225	68	1020	30	100
10"	254	298	17	225	68	1020	12	40

COMMONLY AVAILABLE UPON REQUEST

DIFFERENT DIAMETER
 DIFFERENT COLOR OF RUBBER
 DIFFERENT WORKING PRESSURE
 DIFFERENT LENGHT
 DIFFERENT TEMPERATURE

OIL RETURN HOSE(HARDWALL)

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3/4"	19.1	31.5	21	300	83	1200	60	200
1"	25.4	40	17	250	69	1000	60	200
1-1/4"	31.8	46.5	14	200	55	800	60	200
1-1/2"	38.1	53	10	150	41	600	60	200
2"	50.8	65.5	7	100	28	400	60	200
2-1/2"	63.5	78.5	4	62	17	250	60	200
3"	76.2	91	4	56	15	225	60	200


APPLICATION:

Hardwall hose designed for petroleum and water-bases hydraulic fluids in low pressure and vacuum service.

TEMPERATURE:

-40°C(-40°F) to +100°C(+212°F)

TUBE:

Black, smooth, synthetic rubber.

REINFORCEMENT:

High strength synthetic cord and helix wire.

COVER:

Black, smooth (wrapped finish).
weathering and ozone resistant

WATER DISCHARGE HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	10	150	30	450	60	200
5/8"	15.9	25	10	150	30	450	60	200
3/4"	19.1	28	10	150	30	450	60	200
7/8"	22.2	31	10	150	30	450	60	200
1"	25.4	34	10	150	30	450	60	200
1-1/8"	28.6	38	10	150	30	450	60	200
1-3/16"	30.2	40	10	150	30	450	60	200
1-1/4"	31.8	42	10	150	30	450	60	200
1-5/16"	33.3	43	10	150	30	450	60	200
1-3/8"	34.9	45	10	150	30	450	60	200
1-1/2"	38.1	48	10	150	30	450	60	200
1-9/16"	39.7	50	10	150	30	450	60	200


APPLICATION:

Softwall hose designed for water, and non-corrosive fluids used in construction sites and light duty industrial applications.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, synthetic Rubber.

REINFORCEMENT:

High strength synthetic cord.

COVER:

Black, smooth (wrapped finish),
rubber, weathering and ozone resistant.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1-5/8"	41.3	52	10	150	30	450	60	200
1-3/4"	44.5	55	10	150	30	450	60	200
1-7/8"	47.6	59	10	150	30	450	60	200
2"	50.8	62	10	150	30	450	60	200
2-1/8"	54	66	10	150	30	450	60	200
2-1/4"	57.2	69	10	150	30	450	60	200
2-5/16"	59	71.5	10	150	30	450	40	130
2-3/8"	60.3	72	10	150	30	450	60	200
2-1/2"	63.5	76	10	150	30	450	60	200
2-5/8"	66.7	78	10	150	30	450	40	130
2-3/4"	69.9	82	10	150	30	450	40	130
2-7/8"	73	86	10	150	30	450	60	200
3"	76.2	89	10	150	30	450	60	200
3-1/8"	79.4	94	10	150	30	450	40	130
3-1/2"	88.9	103	10	150	30	450	60	200
3-5/8"	92	106	10	150	30	450	40	130
3-3/4"	95	109	10	150	30	450	*	*
4"	101.6	116	10	150	30	450	60	200
4-3/8"	111	126	10	150	30	450	40	130
4-1/2"	114.3	129	10	150	30	450	30	100
5"	127	142	10	150	30	450	30	100
5-1/2"	140	154	10	150	30	450	30	100
6"	152.4	167	10	150	30	450	30	100
6-5/8"	168.3	184	10	150	30	450	30	100
7"	178	194	10	150	30	450	30	100
8"	203.2	219	10	150	30	450	30	100
8-5/8"	219.1	235	10	150	30	450	30	100
10"	254	272	5	75	15	225	12	40
12"	304.8	323	5	75	15	225	12	40

COMMONLY AVAILABLE UPON REQUEST
 DIFFERENT DIAMETER
 DIFFERENT COLOR OF RUBBER
 DIFFERENT WORKING PRESSURE
 DIFFERENT LENGHT
 DIFFERENT TEMPERATURE

WATER SUCTION AND DISCHARGE HOSE

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	21	10	150	30	450	60	200
5/8"	15.9	25	10	150	30	450	60	200
3/4"	19.1	29	10	150	30	450	60	200
7/8"	22.2	31	10	150	30	450	60	200
1"	25.4	35	10	150	30	450	60	200
1-1/8"	28.6	38	10	150	30	450	60	200
1-3/16"	30.2	40	10	150	30	450	60	200
1-1/4"	31.8	42	10	150	30	450	60	200
1-5/16"	33.3	43	10	150	30	450	60	200
1-3/8"	34.9	45	10	150	30	450	60	200
1-1/2"	38.1	48	10	150	30	450	60	200
1-9/16"	39.7	50	10	150	30	450	60	200
1-5/8"	41.3	52	10	150	30	450	60	200
1-3/4"	44.5	56	10	150	30	450	60	200
1-7/8"	47.6	60	10	150	30	450	60	200
2"	50.8	63	10	150	30	450	60	200
2-1/8"	54	66	10	150	30	450	60	200
2-1/4"	57.2	69	10	150	30	450	60	200
2-5/16"	59	72.5	10	150	30	450	40	130
2-3/8"	60.3	74	10	150	30	450	60	200
2-1/2"	63.5	77	10	150	30	450	60	200
2-5/8"	66.7	80	10	150	30	450	40	130
2-3/4"	69.7	84	10	150	30	450	40	130
2-7/8"	73	88	10	150	30	450	60	200
3"	76.2	90	10	150	30	450	60	200
3-1/8"	79.4	95	10	150	30	450	40	130
3-1/2"	88.9	104	10	150	30	450	60	200
3-5/8"	92	107	10	150	30	450	40	130



APPLICATION:

Hardwall hose designed for suction and discharge of water and non-corrosive fluids used in construction sites and light duty industrial applications.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, smooth, synthetic rubber.

REINFORCEMENT:

High strength synthetic cord and helix wire.

COVER:

Black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant.

OPTIONAL REQUEST:

Corrugated (wrapped finish); Cuffed ends in different length.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
3-3/4"	95	111	10	150	30	450	*	*
4"	101.6	118	10	150	30	450	60	200
4-3/8"	111	127	10	150	30	450	40	130
4-1/2"	114.3	130	10	150	30	450	30	100
5"	127	145	10	150	30	450	30	100
5-1/2"	140	158	10	150	30	450	30	100
6"	152.4	170	10	150	30	450	30	100
6-5/8"	168.3	186	10	150	30	450	30	100
7"	178	198	10	150	30	450	30	100
8"	203.2	224	10	150	30	450	30	100
8-5/8"	219.1	239	10	150	30	450	30	100
10"	254	278	10	150	30	450	12	40
12"	304.8	328	10	150	30	450	12	40

LAY FLAT WATER DISCHARGE HOSE								
I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1/2"	12.7	20	10	150	30	450	60	200
5/8"	15.9	23.3	10	150	30	450	60	200
3/4"	19.1	26.5	10	150	30	450	60	200
7/8"	22.2	30	10	150	30	450	60	200
1"	25.4	32	10	150	30	450	60	200
1-1/8"	28.6	35	10	150	30	450	60	200
1-3/16"	30.2	38	10	150	30	450	60	200
1-1/4"	31.8	39	10	150	30	450	60	200
1-5/16"	33.3	41	10	150	30	450	60	200
1-3/8"	34.9	43	10	150	30	450	60	200
1-1/2"	38.1	46	10	150	30	450	60	200
1-9/16"	39.7	47.5	10	150	30	450	60	200


APPLICATION:

Lightweight and lay flat softwall hose designed for the discharge of waste water domestic applications.

TEMPERATURE:

-20°C(-4°F) to +70°C(+158°F)

TUBE:

Black, Smooth, Synthetic Rubber.

REINFORCEMENT:

High strength synthetic cord.

COVER:

Black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant.

I.D.		O.D.	WORK PRESURE		BURST PRESURE		MAX. LENGTH	
INCH	MM	MM	BAR	PSI	BAR	PSI	M	FT
1-5/8"	41.3	49	10	150	30	450	60	200
1-3/4"	44.5	52.5	10	150	30	450	60	200
1-7/8"	47.6	55	10	150	30	450	60	200
2"	50.8	58	10	150	30	450	60	200
2-1/8"	54	62	10	150	30	450	60	200
2-1/4"	57.2	65	10	150	30	450	60	200
2-3/8"	60.3	68	10	150	30	450	40	130
2-1/2"	63.5	72	10	150	30	450	60	200
2-5/8"	66.7	75	10	150	30	450	60	200
2-3/4"	69.9	77.5	10	150	30	450	40	130
2-7/8"	73	81	10	150	30	450	40	130
3"	76.2	85	6	90	18	270	60	200
3-1/8"	79.4	88	6	90	18	270	40	130
3-1/2"	88.9	98	6	90	18	270	60	200
4"	101.6	110	6	90	18	270	60	200
4-1/2"	114.3	123	6	90	18	270	30	100
5"	127	137	6	90	18	270	30	100
6"	152.4	164	6	90	18	270	30	100
6-5/8"	168.3	181	6	90	18	270	30	100
8"	203.2	217	6	90	18	270	30	100
8-5/8"	219.1	233	6	90	18	270	30	100
10"	254	268	5	75	15	225	12	40
12"	304.8	319	5	75	15	225	12	40



The Global leader for Rubber Hoses.

MHM Consortium Sdn. Bhd.

**D-3A-12, Capital 4, Oasis Square, No. 2, Jalan PJU 1A / 7A,
47301 Petaling Jaya, Selangor. Malaysia.**

Tel: +603 7734 4141, Mobile: +6012 320 6840

Fax: +603 7734 1945

Email : sales@maraton.com.my

Website: www.maraton.com.my